## dreamscape

## DLED-7300A-SQ2" SORAA Vivid LED Downlight


9.5W 1-Light Scoop Wall Wash Recessed Trim Lamping: 1 x 9.5W max. SORAA Vivid LED. CRI: 95

| PROJECT TYPE  | CATALOG NUMBER |  |
|---|----------------|--|
|   |                |  |
| PROJECT The   Trim Description: Recessed 1-light, 9.5W SORAA Vivid LED, square 2" pinhole trim. Allows for 45° vertical adjustment with 365° horizontal rotation. Suited for steep slope ceilings. For use with Dreamscape Lighting's DLED-7001 Non-IC and DLED-7005-IC and IC-AT housings.   Mechanical: Fixture housing is 18 ga. CRS nad features two 1 ga. adjustable steel hanger bars which can be extended to 23.5". Access below ceiling. Ceiling trim flange is provided with .5" plaster lip with centerline notches for precise trim alignment.   Electrical: Housing is ETL listed for through branch circuit wiring. Housing features integral electronic transformer. Secondary lead is 12V. Primary lead is 120V. Access above ceiling is not required.   Lamping: Utilizes 9.5W SORAA Vivid MR-16 LED lamp. With a CRI of 95, rich saturated color rendering, and excellent color stability. Light output the equivalent to 35W MR-16. Dimmable (see below).   Finish: Entities |                |  |
| Standard trim finish is powder coated semi-gloss white. Matte black is standard<br>for trim inner core. See below for other finishes. Custom finishes available, please   | VIVID          |  |
| consult factory.  |                |  |
| Labels:<br>FTL - Suitable for damp location   |                |  |
| Standard trim finish is powder coated semi-gloss white. Matte black is standard for trim inner core. See below for other finishes. Custom finishes available, please consult factory.<br>Labels:  |                |  |

ETL - Suitable for damp location. **Dimming:** 

Available using ELV or Reverse Phase with neutral.

| SORAA LED MR16 Sp  | ecs                          |
|--------------------|------------------------------|
| Voltage            | 12VDC                        |
| Watts              | 9.5W                         |
| Lumens             | 2700K: 400                   |
|                    | 3000K: 420                   |
| Color Temperature  | 2700K, 3000K                 |
| Beam Spread        | FL (36°), NFL (25°), S (14°) |
| CRI                | 95                           |
| Halogen Equivalent | 35W                          |
| Warranty           | 3 years / 35,000 hours       |



— 2" SQ. — 5.375" SQ.

000

4.50'

For Use with the Following Dreamscape Housings

| Catalog No.<br>DLED-7300A  | Trim Mounting<br>FT        | Color Temp.<br>2700K | Beam Spread<br>FL   | Finish<br>White   | Adjustability                   | Construction   | Lamp                       |
|--|----------------------------|----------------------|---|---|---------------------------------|--|----------------------------|
| DLED-7300A-SQ2"<br>DLED-7300A-SQ2"-1<br>DLED-7300A-SQ2"-2<br>DLED-7300A-SQ2"-3<br>DLED-7300A-SQ2"-3<br>DLED-7300A-SQ2"-5<br>DLED-7300A-SQ2"-6<br>DLED-7300A-SQ2"-7 | <b>FT</b><br>Flush<br>Trim | 2700K<br>3000K       | FL<br>Flood 36°<br>NFL<br>Narrow Flood 25°<br>S<br>Spot 14° | White<br>Verdè<br>Satin Nickel<br>Copper Bronze<br>Custom<br>Ancient Bronze<br>Brass Bronze<br>Copper Plate | 45° Vertical<br>365° Horizontal | Powder Coat Steel<br>Solid Brass<br>Solid Brass<br>Solid Brass<br>Custom Powder Coat<br>Solid Brass<br>Solid Brass | Soraa<br>Vivid<br>9.5W Led |

Ordering Example: DLED-7300A-SQ2"-6-FT-2700K-NFL

©2014 Dreamscape Lighting Specifications are subject to change without notice. 5521 Washington Blvd. Los Angeles, CA 90016 Telephone: (323) 933-5760 FAX: (323) 933-3607 www.dreamscapelighting.com info@dreamscapelighting.com

